

ASP 66 Shingle Delivery



The ASP models are mobile and height-adjustable, shingle stream deliveries with an integrated pressing station and integrated batch offsetting feature making them ideal for small to medium circulations. The simple shingle method is the most versatile slow down delivery available and can work with nearly any product and nearly any configuration. There is a low marking risk so it is well suited for sensitive and freshly printed products. These features make them perfect for systems with frequent production line changeovers and a wide variety of applications.

Features & Benefits

- Inline, offline, or nearline operation for flexible finishing setups
- Integrated two-station pressing removes air for flatter, higher-quality signatures Standard 2-up production with optional 3-up or 4-up configurations
- Spreading belts and shingled delivery ensure smooth, controlled product handling
- Adjustable waterfall height for optimal pressing and flow control
- Built-in marking device, light barrier, and counter for accurate batch management
- Large laydown table supports continuous, high-volume production
- Rugged, low-maintenance design built for 24/7 commercial print environments
- Fast makeready and simple operation for a wide range of applications

Specifications

- Maximum Working Width without ME: 26
- Maximum Working Width with ME: 23 $\frac{3}{4}$ "
- Minimum Infeed Height: 15 $\frac{3}{4}$ "
- Maximum Infeed Height: 37 $\frac{3}{8}$ "
- Minimum Loading Height: 19 $\frac{5}{8}$ "
- Maximum Loading Height: 35 $\frac{3}{8}$ "